



	PL65-12	PL65-15
--	---------	---------

Technical specifications

Mounting	Panel	
Ingress protection	IP 65	
Display size (diagonal)	310 mm. (12.1")	380 mm. (15. 0")
LCD Display	TFT active matrix	
Number of pixels (W x H)	800 (W) x 600 (H)	1024 (W) x 768 (H)
Pixel pitch	0.3075 mm.	0.297 mm.
Number of colours	262,44 (max)	262,144 (max)
Luminance	>250 cd/m ²	>200 cd/m ²
Active area (W x H)	246 (W) x 184.5 (H) mm.	304.1 (W) x 228.1 (H) mm.
Viewing angle	40° upward 50° downward 140° horizontal angle	120° vertical angle 140° horizontal angle
Backlight	CCFL (Twin Lamp) - 50.000 P.O.H.	
Standard interface	Analogue D-SUB 15 pin	
Power consumption	< 15W operating mode	< 50W operating mode
Power supply	110-220 V/AC (autoranging 50/60 Hz)	
Dimensions (w x h x d)	345 x 266.5 x 71 mm.	421 x 337 x 76.5 mm
Weight	4.5 Kg	5.8 Kg

Options

Power supply	24 V/DC
Touch screen	5-Wire resistive
Backlight replacement kit	Yes

Environmental

Relative humidity	max 80% non condensed
Storage temperature	-20°C to +60°C
Operating temperature	0°C to 40°C

